

HASCISE HANDHELD TERMINAL



TECHNICAL SPECIFICATIONS

ABS Case: IP54 **Protection:**

-20 °C to 50 °C ** Operating temperature: 10 °C to 40 °C Charging temperature: -20 °C to 20 °C Storage temperature:

56 x 45 x 14 mm (L x W x H) **Dimensions:**

Weight: 45 g

Battery, li-po with 1.66 Wh (450 mAh/3.7 V), Docking station Power supply:

Status LED Display:

Keyboard: On/Off Button & Scanner Button

2D scanner (SE4770) integrated in housing Barcode scanner:

Optional: DotCode Scanner

Interfaces: BT-compatible close-range network 4.0

Compatibility with all BT-enabled devices: BT 4.0 and above



SPECIAL FEATURES

- Scan trigger via configurable infrared proximity sensor & scanner key
- Scan feedback via LED, Sound & Vibration
- Pairing via BT-compatible close-range network
- Easy pairing via ACD 'EasyToConnect' App



2 Hasci units shown in double charging cradle

COMPATIBILITY WITH ACD DEVICES:

- M2SmartSE Handheld Terminal
- M270 Handheld Terminal
- Vehicle Terminal MFT series



Hasci three quarter view

ACCESSORIES

- Docking station: DSHasciSE
- ACD Wrist Strap incl. Finger Switch
- HasciSE mounting plate
- HasciSE Zipper-Strip (Square Connector)
- HasciSE Zipper-Strip (Round Connector)



Hasci connectors

















